

## PPS31 Wellhead Pressure Logger

The **PPS31 Wellhead Pressure Logger** is a programmable gauge that samples pressure and temperature providing real time monitoring. The logger has a highly viewable LCD display where data can be read and also has built in memory. The intrinsically safe design means this logger can be used in hazardous areas.

### Applications:

- Gas Wellhead Build-up Tests
- Stimulation Monitoring
- Pipeline Monitoring
- Fracture Monitoring
- Wellhead Monitoring
- Injection Pressure Monitoring



### Sensor Type

Silicon-Sapphire

### Pressure

Range-psi	Up to 15 kpsi
Accuracy-psi	± 0.03% FS
Resolution-psi	0.0003% FS
Drift-psi/year	<3

### Temperature

Sensor Rating-°C	-20 (-4 °F) to 70 (158 °F)
Accuracy-°C	± 0.5
Resolution-°C	0.01
Environmental Temperature-°C	-40 (-40 °F)~ 70 (158 °F)*

### Characteristics

Service	Sour Services (available upon request)
Power Source	Lithium Battery Pack
Data Set	Time / Pressure / Temperature
Data Receiving Mode	Wireless (915 MHz, ISM)
Wireless Transmission Distance	328' (100 m)
Overall Length-inches	14 (356 mm)
Work Mode	MRO / SRO
Sample Rate	1 sec to 18 hours per sample
Memory Capacity	Optional 1M, 2M or 4M data sets
Connection	3/4" NPT/Autoclave
Safety Rating	Class I, Div 1, Group A, B, C and D T4 (CAN & USA) Exia IIC T4 (for Canada) LT1624 Class 1, Zone 0 AEx ia IIC tT4 (for USA only) Ambient Temperature -40 °C.-55 °C)

LCD Display environmental temperature is -20 °C -70 °C  
Wireless is Optional

